



CULTURE OF SOUND



WCX SERIES CATALOGUE

LATEST EDITION

WCX Series

WEATHER-RESISTANT COAXIAL CABINET

The WCX Series have been designed to offer the utmost sound quality for indoor and outdoor installations.

These cabinets are weather resistant speakers, designed to withstand harder weather conditions, where the cabinets are exposed to the elements.

Weight has been left as low as possible providing easy set ups in fixed installation as well as easy transport. It can also be powered from an external amplifier using the ARK optimised preset.

The enclosure is made from premium grade birch plywood and finished with a polyurea coating for longer durability & weather protection.



PA system



Public address



Convention centers



Houses of worship



Background music



Commercial complex

WCX- 8



The WCX-8 is a two-way coaxial speaker designed for outdoor applicatios. Line transformer optional.

This is a weather resistant speaker, designed to withstand harder weather conditions, where the cabinets are exposed to the elements.portable applications.

The WCX-8 is a two-way coaxial speaker designed for outdoor applicatios. Line transformer optional.

This is a weather resistant speaker, designed to withstand harder weather conditions, where the cabinets are exposed to the elements.

The WCX-8 has a stainless steel 1 mm grill also available in aluminum with protective layer and micro textured paint and a weatherstrip edging for extreme protection.

This enclosure has an acoustex filter, a hydrophobic polyester sheet to prevent the penetration of water and external elements produced by extreme weather conditions. Also, 35 ppi Acoustic foam to protect against dust particles, M8 stainless steel 316 L screws and a waterproof protected cone on both sides.

An aluminum back plate with pressure gland is included for an extra tight connection and easy installation.


Components	1 x 8" coaxial speaker with LF 2.5" and HF 1.75" voice coil
Max SPL	120 dB - 126 dB Peak
Coverage	70° conical dispersion
Power	300 W AES (600 W program, 1200 W Peak)
Operating mode	8 Ω / Optional 100 V: 200 W / 100 W / 50 W selectable
Connectors	In: Euroblock terminal / Out: Cable gland
Dimensions	265 x 265 x 265 mm (H x W x D)
Weight	10 Kg (22 lbs)



LYNX

pro-audio

CULTURE OF SOUND



www.lynxproaudio.com